



已确认此版本的所有图纸
 客户签名: _____ 日期: _____

REV	DESCRIPTION	DATE
0.1	首次设计	2022-8-12
0.1	更换背光	2022-8-09

PIN	SYMBOL
1	GND
2	GND
3	NC
4	IM0
5	IM1
6	RESET
7	DB17
8	DB16
9	DB15
10	DB14
11	DB13
12	DB12
13	DB11
14	DB10
15	DB9
16	DB8
17	DB7
18	DB6
19	DB5
20	DB4
21	DB3
22	DB2
23	DB1
24	DB0
25	RD
26	WR
27	RS
28	CS
29	IOVCC
30	IOVCC
31	VCC
32	VCC
33	NC
34	LEDA
35	LEDK
36	VS
37	TE
38	NC
39	GND

Notes:

1. Display Mode: 262K TFT/Normally Black
2. Viewing Angle: ALL
3. LCD Driver IC: 7796
4. Operating Temp: -20°C ~ +70°C
5. Storage Temp: -30°C ~ +80°C
6. *: Critical Dimension, (): Reference Dimension
7. Undefined Tolerance: ±0.2
8. Requirements on Environmental Protection: ROHS

Kingtech Group Co., Ltd

TITLE:	ASSEMBLY	DΦ NOT SCALE THIS DRAWING. GENERAL TOLERANCE: ±0.2	
PART NO.:	PV03522H0139V		
DESIGNED BY:	DATE:	PROJECTION:	
CHECKED BY:	DATE:	SCALE: N.T.S	
APPROVED BY:	DATE:	SHEET: 1 OF 1	

1 UNIT: mm